

AUTOMATIC TRANSMISSION FLUID

Motosel Full Synthetic Multi-Vehicle Automatic Transmission Fluid provides extreme transmission protection including additional oxidation control, excellent low temperature and superior shear stability performance in modern passenger car, flex-fuel vehicle, hybrid, truck, and sport utility vehicle transmissions. It is suitable for use in high performance automatic transmissions calling for GM DEXRON®-VI, DEXRON® II/III/III/IIH, Ford MERCON®LV, Allison C-3 & C-4, CAT TO-2, Chrysler ATF+3+4, Honda Dual Pump, Z-1, DW-1, Hyundai/Kia SP-II/III/IV, JASO 1A, 2A, Nissan Matic Fluids, Toyota T-III, T-IV, WS and many other American, Asian and European OEM's performance standards including Mercedes Benz NAG 1, MAN 339A, Mazda, Mitsubishi, Subaru, Porsche, Voith 55.6335, VW, ZF TE-ML 21L, ZF 8 & 9 speed and BMW 4- and 5-speed automatic transmission specifications.

Benefits and Applications

- Superior friction retention and smooth shifting
- Advanced additives protect against rust, corrosion and foam
- Enhanced oxidative stability for longer fluid life and extended service interval
- Excellent extreme pressure and anti-wear performance and protection
- Enhanced oxidative stability for longer fluid life and extended service interval
- Wide range of seal compatibility for better leakage prevention

Suitable for:

- GM DEXRON®-VI, DEXRON® III/III(H)/IIE
- Ford MERCON®
 - Nissan® Matic Fluids
 - Hyundai/Kia SP-II/III/IV
 - Toyota WS, T-III, T-IV
 - Mercedes Benz®
 - Allison® C-3, C-4
 - Volvo CE 97340
 - ZF TE-ML-14A
 - Honda® Z-1



- #M-0024 / 1Qt
- #M-0620L / 1L
- #M-0228 / 5Qt
- #M-0068 / 5Gal
- #M-0341 / 16Gal
- #M-0380 / 22.7L
- #M-0067 / 55Gal
- #M-0087 / Bulk

TYPICAL CHARACTERISTICS - MV ATF

SAE GRADE	TEST METHOD	MV ATF
Colour	Visual	Red
Viscosity @ 100°C, cSt	ASTMD 445	7.0
Viscosity @ 40°C, cSt	ASTMD 445	32.9
Viscosity Index	ASTMD 2270	180
Pour Point, °C/°F	ASTMD 97	-51/-59.8
Flash Point, COC °C/°F	ASTMD 92	204 / 399.2
API Gravity	ASTMD 1298	32.6
Brookfield Vis.cP @ -40°C	ASTMD 2983	16200

Typical test data are average values only. Minor variations, which do not affect performance, may occur. You should consult your owner's manual to verify proper fluid recommendation for your particular vehicle.

HANDLING AND SAFETY INFORMATION - Refer to MOTOSEL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.