

Motosel 2-Cycle

SYNTHETIC BLEND

UNIVERSAL MULTI-PURPOSE ENGINE OIL

Motosel 2 Stroke Motor Oil synthetic blend is formulated with ashless detergents for maximum performance and minimum ring sticking, piston burning and spark plug fouling. It provides advanced anti-scuff, anti-wear and corrosion protection. It is specifically designed for outboard motors.

Motosel 2 Stroke motor oil's exclusive additives meet or exceed the industry standard

- Guarding against power robbing ring stick and carbon build up
- Providing superior anti-wear and anti-corrosion protection in the harsh marine environment
- Prevents varnish and wear

Ready for extended full-throttle operation, punishing hole shot power, hours of trolling or everyday operation

Ratio / Rapport	Fuel-oil Mixture / Mélange de carburant et d'hulle				
		50:1	40:1	32:1	25:1

UNIVERSAL MULTI-PURPOSE OIL FOR AIR COOLED ENGINES



#M-0627L / 1L
#M-0160 / 5Gal

TYPICAL CHARACTERISTICS - 2-CYCLE ENGINE OIL

Typical Properties	
Flash Point	405 °F
Boiling Point	Not Determined
Specific Gravity	.91
Appearance	Light Blue
Odor	Mild Petroleum
Flammability	Low Flammability
Plastic Safe	Yes
Propellant	Not Applicable

Typical test data are average values only. Minor variations, which do not affect performance, may occur. As always, you should consult your owner's manual to verify the proper oil recommendation for your particular vehicle.

HANDLING AND SAFETY INFORMATION - Refer to MOTOSEL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.



WWW.MOTOSEL.COM
INFO@MOTOSEL.COM
+1-888-668-6463