

Motosel SAE 0W-40

FULL SYNTHETIC PASSENGER CAR MOTOR OIL

Motosel Full Synthetic SAE 0W-40 Motor Oil is a superior quality multi-grade motor oil designed with a state-of-the-art low friction additive system for maximum engine protection even under the toughest driving conditions. It outperforms conventional motor oil, reduces friction and wear at start-up and protects your engine against performance robbing sludge and varnish deposits. Motosel Full Synthetic Motor Oil is recommended for turbo-charged and high-powered passenger car, truck, sport utility vehicle and other mobile or stationary engines.

Motosel Full Synthetic SAE 0W-40 Motor Oil meets or exceeds American Petroleum Institute (API) SP service classification and is compatible with all prior API categories. Motosel Full Synthetic SAE 0W-40 Motor Oil has been field tested to be comparable to most American, Asian and European manufacturers' standards including VW 502 /505, MB 229.3, and many other OEM's specifications where a full synthetic API SP motor oil is recommended.

Benefits and Applications

- Designed especially for European gasoline and diesel engines
- More robust oil for longer drain intervals
- Enhanced oxidative stability, emission system and wear protection
- Maximum engine wear, corrosion, and rust protection and cleanliness
- Aggressive resistance to sludge and varnish deposits formation
- Lower pour point reduces start-up wear during cold weather

Meets the following performance specification :

API SP
VW 502 / 505, MB 229.3



TYPICAL CHARACTERISTICS - 0W-40

SAE GRADE	FULL SYN	0W-40
API SERVICE		SP
API Gravity	ASTM D287	35.0
Flash Point, COC °C/°F	ASTM D92	201 / 394
Pour Point, °C/°F	ASTM D97	-48 / -54.4
Viscosity @ 40°C, cSt	ASTM D445	86.2
Viscosity @ 100°C, cSt	ASTM D445	15.1
Viscosity Index	ASTM D2270	185
CCS, mPa·sec °C max	ASTM D5293	6200 @ -35
Total Base No. TBN	ASTM D2896	7.9

Typical test data are average values only. Minor variations, which do not affect performance, may occur. You should consult your owner's manual to verify proper fluid recommendation for your particular vehicle.

- #M-0578 / 1Qt
- #M-0552 / 4L
- #M-0614L / 1Qt
- #M-0198 / 5Gal
- #M-0615L / 5Qt
- #M-0233 / 16Gal
- #M-0617L / 5Qt
- #M-0197 / 208L Drum

HANDLING AND SAFETY INFORMATION - Refer to MOTOSEL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.



WWW.MOTOSEL.COM
INFO@MOTOSEL.COM
+1-888-668-6463